Watershed Management Checklist for Development Plan Review Floodplain and Stormwater Information

	YES	NO
Site Location Location of development in a Watershed Master Plan Basin		
Location of development in a "New Growth Area" (as defined by the flood		
standards)		
General Drainage		
Area of development contains a stream which drains more than 150 acres or		
has a defined bed and bank All Sumps in development have a dedicated everland flow path for the 100.		
All Sumps in development have a dedicated overland flow path for the 100 year storm event.		Ш
Flow direction arrows are shown on lot lines with less than a 2% slope		
Detention		
Drainage areas for detention calculations are shown on the development		
plan		
Curve number calculations are shown for each sub area Time of concentration calculations are shown for each sub area	H	H
Pre-development and Post-development 2, 10, and 100 year stormwater	H	H
flows are shown for the development	Ш	ш
Post-development stormwater flow rates are not greater than pre-		
development stormwater flow rates		
A detail of the outlet structure is included Dry detention group have a minimum 20% slong the bettern of the		님
Dry detention areas have a minimum 2% slope along the bottom of the pond.		Ш
Detention embankments have 4:1 slope or flatter		
Detention embankments have a minimum 14 foot top width		
Detention areas have maintenance access		
All flow that by-passes the detention area has been accounted for in the detention calculations		Ш
detention calculations		
Stormwater Pipe System		
Drainage areas are shown for the preliminary pipe sizing calculations	\mathbb{H}	\mathbb{H}
Appropriate coefficients are assigned to pipe sizing drainage areas Appropriate design storm (5 or 10 year) was used to size the pipe system	H	H
The 100 year storm calculations are included to show that the 100 year	H	H
storm is contained within the public ROW.		ш
If connecting to an existing pipe system an appropriate investigation was		
done to determine the capacity of the existing system.	_	
The 100 year flow is routed thru the detention area or over detention is		
provided for flows that by-pass the detention area.		
Outlets are placed in channels or swales that are adequate for accepting the design discharge		Ш

	YES	NO
Minimum Opening Elevations Minimum opening elevations above the 100 year storm elevation are shown for all lots adjacent to detention areas, streams, swales, and/or overland flow paths.		
Minimum Flood Corridors Easement dedicated for all streams which drain more than 150 acres or have a defined bed and bank (except for corridors in the FEMA floodplain in "Existing Urban Area"		
Sequencing documentation provided for encroachments into minimum flood corridors		
Existing Urban Area Floodplain/Floodprone Areas FEMA floodplain and/or floodprone areas are shown on the grading and drainage plan and the site plan.		
FEMA floodway shown on the grading and drainage plan FEMA cross sections are shown on grading and drainage plan Lowest finished floor elevations above the 100 year flood elevation are shown for lots in the 100 year floodplain		
New Growth Area Floodplain FEMA floodplain and/or floodprone areas are shown on the grading and drainage plan.		
FEMA floodway shown on the grading and drainage plan FEMA cross sections are shown on grading and drainage plan Lowest finished floor elevations are given for lots in the 100 year floodplain		
Areas and amounts of compensatory storage are shown on the plan. Hydraulic analysis showing no net rise included with the drainage study If within a master planned basin, No Net Rise for the 2, 10 and 100 year storm events.		
All information required by Sec. 10.5 of the Flood Design Criteria are provided.		
Hydraulic analysis with sequencing approach included in the drainage study for all stream crossing structures		
Appropriate mitigation shown for rise caused by stream crossing structures		